



# MS-602 MS POLYMER SEALANT - LOW MODULUS







# 1. Product & Company Identification

**Product Details** 

Product name: MS-602 MS Polymer Sealant- LM

Physical form:

Odour:

Colour:

CAS No.:

Paste

Odourless

Various

Mixture

**Company Details** 

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,

81100 Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545/ + 60-7-3337919

# 2. Hazard(s) Identification

# Hazard Pictogram

None

Signal word: None

GHS Classification:

Not hazardous

#### <u>Precautionary Statement - Prevention</u>

No precautionary statement

#### <u>Precautionary Statement - Response</u>

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN - Wash with soap and water.

P305+P351+P338 IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.







# MS-602 MS POLYMER SEALANT - LOW MODULUS







P333+P313 If skin irritation or a rash occurs - Get medical advice/attention. P337+P313 If eye irritation persist - Get medical advice/attention.

<u>Precautionary Statement – Storage</u>

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement

# 3. Composition / Hazardous Components

**Chemical Name** CAS No. **WT%** 10 - 30 % Phthalate ester 68515-48-0 Silane 3069-29-2 < 5 % Dibutytin 22673-19-4 < 1 % diacetylacetonate 2768-02-7 < 2 % Silane

\_\_\_\_\_

# 4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with

water and soap.

In case of eyes contact: Immediately flush with water for several minutes, seek

medical advice if necessary.

# 5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media: Unknown

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide

and nitrogen oxides and formaldehyde.







# MS-602 MS POLYMER SEALANT - LOW MODULUS







#### 6. Accidental release measures

Methods for cleaning up: Take up mechanically. Absorb with liquid-binding

material (sand, diatomite, acid binders, universal

binders, sawdust)

Human related safety precautions: Ensure adequate ventilation

# 7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good

ventilation during processing. Wear safety shoes.

Protection against fire/ explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L

drum.

# 8. Exposure control / Personal protection

Ingredients with limited values to be Not indicated.

controlled:

Local exhaust: Recommended General ventilation: Recommended

Hand protection:

Eye protection:

Suitable protective gloves.

Safety/ protective glasses.

Flammability: Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.





# MS-602 MS POLYMER SEALANT - LOW MODULUS







# 9. Physical and Chemical Properties

Form: Paste

Specific gravity: 1.45 ± 0.05
Colour: Various
Odour: Odourless
%Volatile by volume (25°C): < 5%
Solubility in water: Insoluble
Boiling point: Not Applic

Boiling point: Not Applicable. Flash point: Not Applicable. Ignition temperature: Not Applicable.

Solubility in water(20°C): Insoluble

Vapour pressure: Not Applicable.

Solubility in organic solvent: Toluene.

Note: the above information is not intended for use in preparing specification.

# 10. Stability and Reactivity

Chemical stability: Stable

Incompatibility (material to be avoid):

Conditions to be avoid:

Dangerous reactions:

Dangerous products of decomposition:

None known.

None known.

In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and

formaldehyde.





# **MS-602** MS POLYMER SEALANT - LOW MODULUS







# 11. Toxicological Information

Acute toxicity: Not determined

Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization: Sensitization possible by inhalation.

Additional Toxicological information: Until more data is known, exposure levels should be maintained

as low as achievable.

#### 12. Ecological Information

No LD<sub>50</sub> data available for the product.

# 13. Disposal considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations. Dispose to an authorised waste collection point.

Mohm Chemical Sdn. Bhd. is an ISO14001 & ISO9001 certified company in Malaysia. x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd. @1993 Mohm Chemical Sdn. Bhd. All rights reserved.

Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.

#### 14. Transport Information

Proper shipping name: Sealant Not available. Hazard technical name: Hazard class: Not available. No dangerous goods under the transport regulation.





# MS-602 MS POLYMER SEALANT - LOW MODULUS







# 15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.