

GASKET SHELLAC

DESCRIPTION:

x'traseal® Gasket Shellac is a hard setting, slow drying liquid designed to coat, seal and repair most gaskets including felt, paper, rubber and composition type gaskets. It seals metal gaskets and threaded connections for light duty service.

FEATURES:

- ◆ Flexible when dry
- ◆ Good fuel resistance
- ◆ Improves reliability
- ◆ Saves time and labor
- ◆ Increases sealing reliability
- ◆ Applies easily
- ◆ Cleans up fast
- ◆ Temperature range -65°F TO +350°F

USES:

- ◆ Apply with brush or roller on dry, clean surfaces, free from dirt, oil, rust and dried paints or sealants. When brushed on gaskets, they should be dry.
- ◆ Xtraseal gasket shellac can be applied at temperatures from 40°F to 100°F
- ◆ The recommended thickness of the film depends on the type of surface. Generally, the wet film should be applied thin (approximately 0.010") and uniform.
- ◆ For bonding gaskets, apply on both surfaces. Allow to dry until surfaces are dry to the touch.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

APPLICATION:

- ◆ Economical sealant for general assembly work
- ◆ Useful on paper, composition, felt and cardboard
- ◆ Hose connections
- ◆ Threaded connections

SPECIFICATION:

Appearance	Viscous liquid
Chemical type	Rosin
Specific gravity	1.00 ± 0.05
Odour	Alcoholic
Color	Yellowish to dark brown

STORAGE:

Material should be stored in a dry and cool place between +5°C to +30°C.

CAUTION:

Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

