

# MC-234

## HI-TECH DUCT SEALANT (SOLVENT BASED)

**DESCRIPTION:**

**x'traseal®** MC-234 Hi-Tech Duct Sealant is a one part solvent base sealant mainly designs for sealing metal duct systems. Its ready-to-use consistency will not drip or run, making application easier and faster. It dries on atmospheric release of the solvent to form a flexible film.

**FEATURES:**

- ◆ Outstanding durability.
- ◆ One parts no mixing.
- ◆ Good adhesion and excellent elasticity to metal duct
- ◆ Permanently flexible under stress to normal expansion and compression.
- ◆ Quick curing at room temperature.
- ◆ Very stable

**USES:**

- ◆ For application at overlapping joints and seams
- ◆ For joints ventilation duct

**WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS**

**NOT RECOMMENDED FOR:**

MC-234 Hi-Tech Duct Sealant is not suitable application on oily substrate, all surface must be thoroughly clean, dry and free from oil, grease and other foreign matter

**APPLICATION:**

- ◆ Surface must be clean and dry.
- ◆ With a spatula/scrapper, apply onto the joint or seam to seal it.
- ◆ Leave it fully dry before apply paint if paint required.

**SPECIFICATION:**

Base	Synthetic Rubber
Appearance	Paste
Solvent	Aromatic Solvent Blend
Specific Gravity	1.15 ± 0.05
Solid Contents	76 ± 5%
Tack Free Time	10 Minutes Approx.
Application Temp.	-10°C To 50°C
Service Temp.	Up To 60°C
Shelf Life	12 Months

**STORAGE:**

Material should be stored in a dry and cool place between +5°C TO +30°C.

**CAUTION:**

Highly flammable. Read and understand material safety data sheet of this product before handling or using.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*

