

PROGLAZE SSG BLACKVersion 5.0
REVISION DATE: 05/14/2015

Print Date 05/15/2015

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : **PROGLAZE SSG BLACK**

Product code : 954802 323

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Black. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Direct contact may cause moderate irritation.
Ingestion : May cause irritation to the mouth, throat and stomach.
Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Possible skin sensitization. As a by-product of curing up to 4% Methyl Ethyl Ketoxime (MEKO) may be released within product. Repeated and prolonged exposure to MEKO can cause allergic skin reaction. It may adversely affect the blood, (methemoglobinemia and anemia). Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Blood, Lung, Liver, Kidney

SECTION 3 - PRODUCT COMPOSITION

| Chemical Name | CAS-No. | Weight % |
|--|-------------------------|-------------|
| Silicone polymer | NJ TSRN# 51721300-5110P | 40.0 - 70.0 |
| Calcium carbonate | 471-34-1 | 15.0 - 40.0 |
| Calcium Carbonate (Limestone) | 1317-65-3 | 10.0 - 30.0 |
| Polydimethylsiloxane, trimethyl endcap | 63148-62-9 | 7.0 - 13.0 |
| Amorphous silica | 7631-86-9 | 3.0 - 7.0 |



PROGLAZE SSG BLACK

Version 5.0
REVISION DATE: 05/14/2015

Print Date 05/15/2015

Carbon Black

1333-86-4

- <1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Silicon oxides and trace amounts of MEKO.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Keep out of water courses. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Store in sealed containers in a cool, dry, ventilated warehouse location.

PROGLAZE SSG BLACK

Version 5.0
REVISION DATE: 05/14/2015

Print Date 05/15/2015

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator, as directed by the manufacturer, when the airborne contaminant level(s) exceed the exposure limits indicated on the MSDS.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

Exposure Limits

| Chemical Name | CAS Number | Regulation | Limit | Form |
|-------------------------------|------------|--|--|--|
| Calcium carbonate | 471-34-1 | OSHA TWA: OSHA TWA: | 15 mg/m3 5 mg/m3 | Total dust. Respirable fraction. |
| Calcium Carbonate (Limestone) | 1317-65-3 | ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA: | 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 | Respirable particles. Inhalable particles. Total dust. Respirable fraction. |
| Amorphous silica | 7631-86-9 | ACGIH TWA: ACGIH TWA: OSHA TWA: | 3 mg/m3 10 mg/m3 0.8 mg/m3 | Respirable particles. Inhalable particles. |
| Carbon Black | 1333-86-4 | ACGIH TWA: OSHA TWA: OSHA TWA: | 3.5 mg/m3 15 mg/m3 5 mg/m3 | Total dust. Respirable fraction. |

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Non-sag gunnable paste
- Color : Black
- Odor : Oxime
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.

PROGLAZE SSG BLACK

Version 5.0
 REVISION DATE: 05/14/2015

Print Date 05/15/2015

Water solubility : Negligible
 Specific Gravity : 1.173
 % Volatile Weight : 1 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.Alcohols.Water or moisture and oxidizing agents.
 Stability : Material is stable under normal storage, handling, and use.
 Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Calcium carbonate, CAS-No.: 471-34-1
 Acute oral toxicity (LD-50 oral) 6,450 mg/kg (Rat) 1,300 mg/kg (Mouse) > 2,000 mg/kg (Rat) > 2,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) > 3 mg/l for 4 h (Rat)
 Acute dermal toxicity (LD-50 dermal) > 2,000 mg/kg (Rat)

Amorphous silica, CAS-No.: 7631-86-9
 Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse) 40,000 mg/kg (Rat) 10,000 mg/kg (Rat) > 3,160 mg/kg (Mouse) > 5,620 mg/kg (Rat) > 3,300 mg/kg (Rat) > 20,000 mg/kg (Rat) > 5,000 mg/kg (Rat) > 10,000 mg/kg (Rat) > 5,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) > 2.2 mg/l for 1 h (Rat) >= 0.69 mg/l for 4 h (Rat) >= 2.08 mg/l for 4 h (Rat) >= 0.14 mg/l for 4 h (Rat) > 0.69 mg/l for 4 h (Rat) > 0.14 mg/l for 4 h (Rat) > 2.08 mg/l for 4 h (Rat) >= 58.8 mg/l for 4 h (Rat) > 58.8 mg/l for 4 h (Rat)
 Acute dermal toxicity (LD-50 dermal) > 2,000 mg/kg (Rabbit) > 5,000 mg/kg (Rabbit)

Carbon Black, CAS-No.: 1333-86-4
 Acute oral toxicity (LD-50 oral) > 8,000 mg/kg (Rat) > 15,400 mg/kg (Rat) > 10,000 mg/kg (Rat) > 10,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) > 4.6 mg/m3 for 4 h (Rat) > 10 mg/m3 for 4 h (Rat) > 1 mg/m3 for 7 h 4.6 mg/m3 for 4 h (Rat) 1 mg/m3 for 7 h

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

PROGLAZE SSG BLACKVersion 5.0
REVISION DATE: 05/14/2015

Print Date 05/15/2015

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

| | |
|-------------------------------|-----------|
| Calcium carbonate | 471-34-1 |
| Calcium Carbonate (Limestone) | 1317-65-3 |
| Amorphous silica | 7631-86-9 |
| Carbon Black | 1333-86-4 |

OSHA Status: Considered : Irritant
hazardous based on the
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
exempt solvent) : 14 g/l

VOC Method 310 : 1.15 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Carbon Black 1333-86-4

U.S. State Regulations:

MASS RTK Components : Calcium carbonate 471-34-1



PROGLAZE SSG BLACK

Version 5.0
 REVISION DATE: 05/14/2015

Print Date 05/15/2015

| | | |
|-----------------------|--|-------------------------|
| | Calcium Carbonate (Limestone) | 1317-65-3 |
| | Amorphous silica | 7631-86-9 |
| Penn RTK Components : | Silicone polymer | NJ TSRN# 51721300-5110P |
| | Calcium carbonate | 471-34-1 |
| | Calcium Carbonate (Limestone) | 1317-65-3 |
| | Polydimethylsiloxane, trimethyl endcap | 63148-62-9 |
| | Amorphous silica | 7631-86-9 |
| NJ RTK Components : | Silicone polymer | NJ TSRN# 51721300-5110P |
| | Calcium carbonate | 471-34-1 |
| | Calcium Carbonate (Limestone) | 1317-65-3 |
| | Polydimethylsiloxane, trimethyl endcap | 63148-62-9 |
| | Amorphous silica | 7631-86-9 |
| | Carbon Black | 1333-86-4 |

Components under California Proposition 65:
WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

| | |
|--------------|---|
| Health | 1 |
| Flammability | 0 |
| Reactivity | 0 |
| PPE | |

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- | | |
|--|--|
| ACGIH - American Conference of Governmental Hygienists | PEL - Permissible Exposure Limit |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act |
| DOT - Department of Transportation | RTK - Right To Know |
| DSL - Domestic Substance List | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration | |