REV: 01 DATE: 04 FEBRUARY 2020



B1 PREMIUM MULTI-PURPOSE GREASE

1. Product & Company Identification

Product Details

Product name: B1 Premium Multi-Purpose Grease

Physical form: Paste

Odour: Characteristic

CAS No.: Mixture Flammability: N/A

Company Details

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,

81100 Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram

Not classified as hazardous

Signal Word: NONE. Not hazardous

<u>Classification</u>

Not classified as hazardous

Hazard Statement

Not classified as hazardous

<u>Precautionary Statement - Prevention</u>

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P281: Use personal protective equipment as required

Precautionary Statement - Response

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P308+P313: If exposed or concerned: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, dry sand.

<u>Precautionary Statement - Storage</u>

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

<u>Precautionary Statement – Disposal</u>

P501 - Dispose of contents/container in accordance with regulations made under the control of Pollution & Environmental Protection Acts.





3. Composition / Hazardous Components

Chemical Name
CAS No. WT%

Treated Mineral Oil 101316-72-7 90~95%
12-hydroxystearate Lithium 7620-77-1 5~10%
Diphenylamine, ethylene propylene copolymer 122-39-4 0.3~0.6%

4. First-aid Measures

In case of inhalation: At ambient/normal handling temperatures, minimal or no irritation

due to inhalation of vapor/mist is expected.

In case of ingestion: First aid is normally not required. Seek medical attention if

discomfort occurs.

In case of skin contact: Wash contact areas with soap and water. If product is injected into

or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours

may significantly reduce the ultimate extent of injury.

In case of eyes contact: Flush thoroughly with water. If irritation occurs, get medical

assistance.

5. Fire Fighting Measures

Flammability: Flammable.

Suitable extinguishing media: Foam, Dry chemical powder, Carbon dioxide(CO2)

Unsuitable extinguishing media: Straight Streams of Water

Hazardous decomposition: carbon dioxide, carbon monoxide, metal oxide/oxides

6. Accidental release measures

Personal Precaution: Using suitable protective equipment. In case of large spillage, using

suitable protective clothing, such as overall, gloves and boots in

cleaning procedure.

Remove contaminated clothes as soon as possible.

Environmental Cautions: Prevent spill to enter and spread to drain, water resource and soil.

Contact local environment protection authorities.

Cleaning Method: Land Spill: Allow spilled material to solidify and scrape up with

shovels into a suitable container for recycle or disposal.

Water Spill: Confine the spill immediately with booms. Stop leak if you

can do it without risk. Skim from surface.

7. Handling and Storage

Handling Prevent small spills and leakage to avoid slip

hazard.

Static Accumulator: This material is not a static accumulator.

Storage: Do not store in open or unlabelled containers





8. Exposure control / Personal protection

exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use

explosion-proof ventilation equipment

> checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

levels.

General ventilation: Recommended

Hand protection:

Eye protection:

Suitable protective gloves
Safety/protective glasses.

Respiratory Protection: Use engineering control to maintain adequate ventilation and avoid

oil mist. If engineering controls do not maintain airborne

contaminant concentration at a level which is adequate to protect

worker health, an approved respirator may be appropriate. Recommend wearing purifying dust or most pa ryiculate airpurifying respirators or self-contained breathing apparatus.

9. Physical and Chemical Properties

Form: Paste

Specific Gravity: 0.95g/cm³ at 20°C Colour: Yellow and brown Odour: Characteristic

Solubility in water:

Dropping Point

170°C

Boiling point:

>316°C

Note: the above information is not intended for use in preparing specification

10. Stability and Reactivity

Chemical stability: Stable under normal condition

Conditions to be avoid: Heat, flames, sparks. Contact with incompatible materials

Incompatible materials Strong oxidizing agents. Chlorine

Dangerous reactions: Combustion
Dangerous products of Carbon dioxide

decomposition:



11. Toxicological Information

Route of Exposure Conclusion / Remarks

Inhalation

Toxicity (Rat): LC50 > 5000 Minimally Toxic. Based on assessment of the components.

mg/m³.

Irritation: No end point data. Not determined.

Ingestion

Toxicity (Rat): LD50 > 2000 Minimally Toxic. Based on test data for structurally similar materials.

mg/kg. Skin

Toxicity (Rabbit): LD50 > 2000 Minimally Toxic. Based on test data for structurally similar materials.

manufactus (Rubbil). Lb30 > 2

mg/kg.

available.

assessment of the components.

Eye

Irritation (Rabbit): Data May cause mild, short-lasting discomfort to eyes. Based on assessment

available. of the components.

12. Ecological Information

Summary: The information given is based on data available for the material, the

components of the material, and similar materials.

Mobility: Base oil component -- Low solubility and floats and is expected to

migrate from water to the land. Expected to partition to sediment and

wastewater solids.

Persistence Biodegradation: Base oil component -- Expected to be inherently

/degradability: biodegradable

Bio-accumulation: Base oil component -- Has the potential to bioaccumulation, however

metabolism or physical properties may reduce the bioaccumulation or

limit bioavailability.

13. Disposal considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations.

Dispose to an authorised waste collection point.

Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.

14. Transport Information

LAND (DOT): Not Regulated for Land Transport. LAND (TDG): Not Regulated for Land Transport.

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code.

AIR (IATA): Not Regulated for Air Transport.

15. Regulatory Information

Classified according to European directives on classification of hazardous substances and preparations, not classified as hazardous. No statutory label required.

All components of this material are listed on the EPA/TSCA Inventory of Chemical Substances.





16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of SDS ***