

SAFETY DATA SHEET

REV: 07 DATE: 01 MARCH 2021

x'traseal®

SN-501

100% RTV NEUTRAL SILICONE SEALANT



SIRIM
CERT. TO ASTM C920 : 2014a
CERT. NO : PC004057



SINGAPORE
GREEN
BUILDING
PRODUCT
SGBC
VERY GOOD
SGBP 3973

1. Product & Company Identification

Product Details

Product name: SN-501 100% RTV Neutral Silicone Sealant
Physical form: Paste
Odour: Oxime Odour
CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.
H319 - Causes serious eye irritation

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor Darul Takzim, Malaysia.
Tel: +607 333 1222 Fax: +607 332 0545 / 333 7919
No.43, Jalan Tambur 33/19, Seksyen 33, Shah Alam Technology Park, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.
Tel: +603 5124 0876 / 5124 0878 Fax: +603 5124 0877

Page 1 of 4

Mohm Chemical Sdn. Bhd. is an ISO 9001 certified company in Malaysia.
x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd.
©1993 Mohm Chemical Sdn. Bhd. All rights reserved.
Website: www.xtraseal.com Email : info@mochem.com

SAFETY DATA SHEET

REV: 07 DATE: 01 MARCH 2021

x'traseal®

SN-501

100% RTV NEUTRAL SILICONE SEALANT



SIRIM
CERT. TO ASTM C920 : 2014a
CERT. NO : PC004057



Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Methyl Tri(Methylethylketoxime) Silane	22984-54-9	1 – 8 %
Vinyl Tri(Methylethylketoxime) Silane	2224-33-1	1 – 5 %
Treated Fume Silica	68583-49-3	5 – 15 %
Silicone Polymer	70131-67-8	70 – 80%

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion:

Seek medical advice immediately.

In case of skin contact:

Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact:

Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media:

All standard fire-fighting media.

Unsuitable extinguishing media:

Unknown

Hazardous decomposition:

Carbon dioxide, carbon monoxide, silicone dioxide, nitrogen oxides and formaldehyde.

6. Accidental release measures

Methods for cleaning up:

Take up mechanically.

7. Handling and Storage

Handling:

Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.

Protection against fire/ explosion:

General rules of fire prevention should be observed.

Storage:

Keep container tightly closed and dry.

Cautions:

Extreme heavy in drum form if product packed in 200L drum.



SN-501**100% RTV NEUTRAL SILICONE SEALANT**SIRIM
CERT. TO ASTM C920 : 2014a
CERT. NO : FC004057SINGAPORE
GREEN
BUILDING
PRODUCT
SGBC
VERY GOOD
SGBP 3973**8. Exposure control / Personal protection**

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/protective glasses.
Flammability:	Combustible
Note: Until more data is known, exposure levels should be maintained as low as achievable.	

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.02 ± 0.02
Colour:	Clear and pigmented
Viscosity:	Not indicated
Odour:	Oxime.
VOC content (USEPA Method 24):	< 4 % (as per USEPA Method 24)
Solubility in water:	Insoluble
Boiling point:	Not Applicable
Flash point:	Not Applicable
Ignition temperature:	Not Applicable
Vapour pressure:	Not Applicable
Note: the above information is not intended for use in preparing specification.	

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known.
Conditions to be avoid:	None known.
Dangerous reactions:	None known.
Dangerous products of decomposition:	Ketoxime during curing.

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	Until more data is known, exposure levels should be maintained as low as achievable.



SAFETY DATA SHEET

REV: 07 DATE: 01 MARCH 2021

x'traseal®

SN-501

100% RTV NEUTRAL SILICONE SEALANT



SIRIM
CERT. TO ASTM C920 : 2014a
CERT. NO : PC004057



SINGAPORE
GREEN
BUILDING
PRODUCT
SGBC
VERY GOOD
SGBP 3973

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose to suitable incineration plant.

14. Transport Information

Proper shipping name: Silicone Sealant
Hazard technical name: Not available.
Hazard class: Not available.
No dangerous goods under the transport regulation.

15. Regulatory Information

Labelling (EC): This product is not subject to the labelling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of SDS ***



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor Darul Takzim, Malaysia.
Tel: +607 333 1222 Fax: +607 332 0545 / 333 7919
No.43, Jalan Tambur 33/19, Seksyen 33, Shah Alam Technology Park, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.
Tel: +603 5124 0876 / 5124 0878 Fax: +603 5124 0877

Page 4 of 4
Mohm Chemical Sdn. Bhd. is an ISO 9001 certified company in Malaysia.
x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd.
©1993 Mohm Chemical Sdn. Bhd. All rights reserved.
Website: www.xtraseal.com Email: info@mochem.com