

BT-390

WINDSCREEN SEALANT (BUTYL TAPE)

DESCRIPTION:

x'traseal® BT-390 Windscreen Sealant (Butyl Tape) is a black, non-hardening synthetic rubber based. It is a sticky ribbon type auto glass replacement sealer used for the installation of all gaskets less windshields and backlites. BT-390 offers a fast and clean method for installing the glass. Instantly with superior adhesion. The sealer has excellent compressibility in both low / high temperatures. It is designed to maintain position, permanently sealing and waterproofing between the glass and pinch weld.

SPECIFICATION:

Base	Butyl rubber
Appearance	Black
Hardness IRHD	25 ± 1
Specific gravity	1.4 ± 0.10
Heat resistance	100°C
Water resistance	Excellent
Service temperature	- 20°C to 70°C
Ordor	Non or very little
Adhesion	Good on metal, glass, wood and concrete
Storage	Product is very inert and can last almost indefinitely without deteriorating

APPLICATION:

- ◆ Remove the windshields and old sealant material from surfaces thoroughly.
- ◆ Surface must be clean, dry and free from grease, oil and dirt.
- ◆ Hand pressed the tape into place ground the pinch weld. Replace new setting blocks if original blocks are damaged.
- ◆ Place the windscreen over the tape and apply pressure evenly to ensure water tight achieved.

TIPS:

- ◆ This tape can be used alone or in combination with other sealants, eg. Polyurethane or silicone sealant depending upon the type of installation.
- ◆ In extremely cold weather conditions, it is recommended to warm the butyl tape for the better workability.

CAUTION:

Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

