

1101 LIQUID GASKET

DESCRIPTION:

x'traseal® 1101 LIQUID GASKET is a semi-drying gray liquid gasket that uses rubber as the main ingredients. It is formulated to form a layer thick enough to work efficiently on uneven joint surfaces. It has a distinguishing ability to turn into rubber-like elastic substances with excellent resistance to heat, oil, gasoline and particularly lpg. Ideal for the purpose of making quality gaskets in garages, workshops, homes and do-it-yourself.

FEATURES:

- ◆ A visco-elastic type sealant capable of joining uneven surfaces.
- ◆ Excellent resistance to heat, oil, gasoline and lpg.
- ◆ Easy to apply and allow to automate the production line with labor-saving equipments, markedly improving the work efficiently.
- ◆ Has the property of flowing at room temperature.

USES:

- ◆ For the purpose of making quality gaskets in garages, workshops, homes and do-it-yourself.

We recommend preliminary compatibility tests prior to application to achieve desirable results

APPLICATION:

- ◆ Surfaces must be clean, dry, and free from moisture, grease and other stains before application.
- ◆ Apply a thin and uniform layer of liquid gasket on both mating surfaces.
- ◆ Assemble about 1 minute after application.
- ◆ Application temperature range is from -40°C to +150°C.
- ◆ Seal tightly after use. Store in a cool dry place.

SPECIFICATION:

Appearance	Gray High Viscosity Liquid
Specific Gravity	1.05 ± 0.05
Solid Content	>48%
Main Solvent	Hydrocarbon Solvent
Main Ingredient	Chloroprene Rubber
Dilution	Toluene
Temperature Range	40°C To 150°C
Shelf life	12 months

STORAGE:

Material Should Be Stored In A Dry And Cool Place Between +5°C TO +30°C.

CAUTION:

Read And Understand Material Safety Data Sheet Of This Product Before Handling Or Using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.