

# B-168

## BUTYL SEALANT

**DESCRIPTION:**

**x'traseal® B-168 BUTYL SEALANT** is a one part sealer mainly consists butyl rubber and synthetic resin. Because of relatively low cost, easy workability, minor clean up problem, elastic compounds with permanent flexibility and good weather properties, it is most suitable for water-proofing, dust-proofing and hermetically sealing of containers, automobiles, buildings and various appliances.

**FEATURES:**

- ◆ Low cost.
- ◆ Outstanding durability.
- ◆ One parts no mixing.
- ◆ Good adhesion and excellent elasticity to metals, woods, plastics, glass and many other engineering materials.
- ◆ 100% weather proof.
- ◆ Use without primer.
- ◆ Excellent gunnability.
- ◆ Very stable properties in a composite container.

**USES:**

- ◆ For joints of containers.
- ◆ For joints of automobiles, bus and other vehicles.
- ◆ Sealing of joints between window sash and wall.
- ◆ Sealing of joints in zinc roofs and slate roofs.

**WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS**

**NOT RECOMMENDED FOR:**

B-168 is not suitable for high joint movement substrate.

**COLOUR:**

Grey. Other colour can be manufactured on request.

**APPLICATION:**

- ◆ Surface must be clean and dry.
- ◆ Cut nozzle to desired size.
- ◆ Insert cartridge into caulking gun.
- ◆ Push sealant ahead for uniform bead.
- ◆ Tool within 5 minutes.
- ◆ Clean off excess sealant with mineral spirit.

**SPECIFICATION:**

Base	Butyl Rubber
Appearance	Non-Sagging Paste
Solvent	Organic Solvent
Specific Gravity	1.45 ± 0.10
Solid Contents	85 ± 5%
Shore A Hardness	25 Approx.
Slump	None
Elongation	350% Approx.
Tack Free Time	60 Minutes Approx.
Cure Through Time	None Curing System
Stain	None
Weather Proof	Excellent
Application Temp.	-10°C To 50°C
Service Temp.	-50°C To 100°C
Shelf Life	12 Months

**STORAGE:**

Material should be stored in a dry and cool place between +5°C TO +30°C.

**CAUTION:**

Highly flammable. Read and understand material safety data sheet of this product before handling or using.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*

