

WOOD FILLER

DESCRIPTION:

x'traseal® Wood Filler is a cellulose fibre ready mixed high performance water based filler that give a tough and smooth sandable surface after dried, it can be stained, varnished, painted and act like real wood.

FEATURES:

- ◆ Low odor.
- ◆ Hard and smooth surface.
- ◆ One parts no mixing.
- ◆ Environmental friendly, easily clean up with water before cured.
- ◆ Good adhesion to wood, concrete, metal and marble.

USES:

- ◆ DIY application: furniture, panelling, doors, plywood patching.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

Not for: use in areas of constant water immersion.

Not for: joint movement.

COLOUR:

Natural, teak.

APPLICATION:

- ◆ Surface to be filled must be clean and dry.
- ◆ Mask smooth surface to simplify clean up.
- ◆ Apply wood filler firmly into place with a putty knife.
- ◆ Fill up slightly higher surface to allow for sanding.
- ◆ Sand after 30minutes on shallow repairs, deep repairs after 2-8hours.
- ◆ Use medium sand paper, do not continuous high speed sanding.

CURING TIME:

WOOD FILLER WILL DRIED IN APPROXIMATELY 30 MINUTES AND WILL CURE TO A DEPTH OF 5mm IN 1-2DAYS. LONGER CURING TIME MAY BE NECESSARY IN COLD AND HIGH HUMIDITY AREA.

SPECIFICATION:

Base	Vinyl acetate latex
Appearance	Non-sagging paste
Colour	Natural, teak.
Specific gravity	1.73 ± 0.2
Solid contents	75 ± 2 %
Tack free time	10 minutes approx.
Application temp.	5°C to 50°C
Service temp.	-10°C to 80°C
Shelf life	12 months

STORAGE:

Material should be stored in a dry and cool place between +5°C to +30°C.

CAUTION:

Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.