

TECHNICAL DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

4 STROKE MOTORCYCLE OIL

SAE10W-40(API SL)

4 STROKE MOTORCYCLE OIL SAE10W-40(API SL) A high performance engine oil designed to provide excellent engine protection under the high-heat conditions typical of 4-stroke cycle motorcycle and ATV engines. It features x'traseal exclusive "Low-SAPS" additive technology and a unique anti-wear system.

BENEFITS

- Resists viscosity and thermal breakdown at high temperatures.
- Protects against wear and piston/cylinder scuffing.
- Help minimize the formation of sludge and varnish deposits.
- Resists foaming and air entrainment.
- Meets API SL standards..

TYPICAL PROPERTIES

Characteristic	Unit	ASTM Method	RESULT
Colour	-	D1500	1.5
Kinematic Viscosity @ 100°C	cSt	D445	14.4
Kinematic Viscosity @ 40°C	cSt	D445	106.0
Viscosity Index	-	D2270	139
Flash Point COC, °C	°C	D92	206
Pour Point	°C	D97	-33

Caution: Do not fill container with fuel /solvent- static could cause fire. Avoid prolonged and repeated skin contact with the used oils. Protect the environment by disposing of used oil properly.

