



625°F WHITE RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 04

Date: 30 April 2024

1. Product & Company Identification

Product Details

Product name: 625°F White RTV Gasket Maker (Acetoxy)
Physical form: Paste
Odour: Acetic Acid
Colour: White
CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ +60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.x'traseal.com Email: info@mochem.com



625°F WHITE RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 04

Date: 30 April 2024

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statement – Storage
No precautionary statement.

Precautionary Statement – Disposal
No precautionary statement.

3. Composition / Hazardous Components

Chemical Name	CAS No.	WT%
Titanium dioxide	13463-67-7	< 5 %
Methyltriacetoxysilane	4253-34-3	< 5 %
Treated Fume Silica	68611-44-9	5 – 15 %

4. First-aid Measures

Take off all contaminated clothing immediately.
In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.
Unsuitable extinguishing media: Unknown
Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and acetic acid.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion: General rules of fire prevention should be observed.
Storage: Keep container tightly closed and dry.
Cautions: Extreme heavy in drum form if product packed in 200L drum.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com

Mohm Chemical Sdn. Bhd. is an ISO14001 & ISO9001 certified company in Malaysia. x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd. ©1993 Mohm Chemical Sdn. Bhd. All rights reserved.



625°F WHITE RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 04

Date: 30 April 2024

8. Exposure control / Personal protection

Ingredients with limited values to be controlled:

Local exhaust:

General ventilation:

Hand protection:

Eye protection:

Flammability:

Not indicated.

recommended

recommended

Suitable protective gloves.

Safety/ protective glasses.

Combustible

9. Physical and Chemical Properties

Form:

Paste

Specific gravity:

1.03 ± 0.03

Colour:

White

Viscosity:

Not indicated

Odour:

Acetic Acid

Volatile % (25°C):

< 10%

Solubility in water:

Insoluble

Boiling point:

Non known

Flash point:

Non known

Ignition temperature:

Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:

Stable

Incompatibility (material to be avoid):

Water

Conditions to be avoid:

High temperature

Dangerous reactions:

None known

Dangerous products of decomposition:

Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde

11. Toxicological Information

Acute toxicity:

Not determined

Primary irritant effect,

On the skin:

Irritant for skin and mucous membranes.

On the eye:

Irritant effect

Sensitization:

Sensitization possible by inhalation.

Additional Toxicological information:

When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)

No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,

Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919

Website: www.xtraseal.com Email: info@mochem.com

Mohm Chemical Sdn. Bhd. is an ISO14001 & ISO9001 certified company in Malaysia. x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd. ©1993 Mohm Chemical Sdn. Bhd. All rights reserved.



625°F WHITE

RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 04

Date: 30 April 2024

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of it to suitable incineration plant.

14. Transport Information

Proper shipping name: Silicone Sealant
Hazard technical name: Not available.
Hazard class: Not available.
No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com

Mohm Chemical Sdn. Bhd. is an ISO14001 & ISO9001 certified company in Malaysia. x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd. ©1993 Mohm Chemical Sdn. Bhd. All rights reserved.