

x'traseal®

SAFETY DATA SHEET

REV: 08

Date: 30 April 2024

SN-502

ALL WEATHER SEALANT - LOW MODULUS





1. Product & Company Identification

Product Details

Product name: SN-502 All Weather Sealant - LM

Physical form: Past

Odour: Low Oxime Odour

CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32, JalanTemenggong, Off JalanTampoi,

81100 Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.

H319 - Causes serious eye irritation

Precautionary Statement - Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement - Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)

No. 32, Jalan Temenggong, Off Jalan Tampol, 81100 Johor Bahru, Johor, Malaysia. Tel: +607 333 1222 Fax: +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



x'traseal®

SAFETY DATA SHEET

REV: 08

Date: 30 April 2024

WEATHER SEALANT - LOW MODULUS





P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

<u>Precautionary Statement - Storage</u>

No precautionary statement

Precautionary Statement - Disposal

No precautionary statement

3. Composition / Hazardous Components			
Chemical Name	CAS No.	WT%	
Methyl Tri (Methylethylketoxime) Silane	22984-54-9	1 – 5 %	
Vinyl Tri (Methylethylketoxime) Silane	2224-33-1	1 – 5 %	
Treated Fume Silica	68583-49-3	5 – 15 %	

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion:

Seek medical advice immediately. Wipe with paper towel and immediately clean with water and soap. In case of skin contact: Immediately flush with water, seek medical advice if necessary. In case of eyes contact:

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media:

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides

and formaldehyde.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during

processing. Wear safety shoes.

Protection against fire/ explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Extreme heavy in drum form if product packed in 200L drum. Cautions:



x'traseal®

SAFETY DATA SHEET

REV: 08

Date: 30 April 2024

SN-502

ALL WEATHER SEALANT - LOW MODULUS





8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended General ventilation: Recommended

Hand protection:

Eye protection:

Safety/protective glasses.
Flammability:

Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.

9. Physical and Chemical Properties

Form: Paste Specific gravity: 1.40 ± 0.05 Colour: Matt Black Viscosity: Not indicated Odour: Oxime odour. VOC content (USEPA Method 24): < 5 %

VOC content (USEPA Method 24):

Solubility in water:

Boiling point:

Flash point:

Ignition temperature:

Vapour pressure:

Solubility in organic solvent:

Vapour pressure:

Solubility in organic solvent:

Vapour pressure:

Solubility in organic solvent:

Vapour pressure:

Toluene.

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:
Incompatibility (material to be avoid):
Conditions to be avoid:
Dangerous reactions:

Stable
None known.
None known.
None known.

Dangerous products of decomposition: Ketoxime during curing.

11. Toxicological Information

Acute toxicity: Not determined

Primary irritant effect,
On the skin:

Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization: Sensitization possible by inhalation.

Additional Toxicological information: Until more data is known, exposure levels should be maintained as low

as achievable.

12. Ecological Information

Complete information not yet available.





N-502 WEATHER SEALANT - LOW MODULUS



SAFETY DATA SHEET

REV: 08

Date: 30 April 2024

13. Disposal considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations.

Dispose to an authorised waste collection point.

Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.

14. Transport Information

Dangerous Goods by Road (ADR):

Proper Shipping Name:
Hazard class or division:
Identification number:
Packaging group:

Not regulated
Not regulated
Not regulated

International Air Transportation (ICAO/IATA):
Proper Shipping Name: Not regulated
Hazard class or division: Not regulated
Identification number: Not regulated
Packaging group: Not regulated

Water Transportation (IMO/IMDG):

Proper Shipping Name:
Hazard class or division:
Identification number:
Packaging group:

Not regulated
Not regulated

Not dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labelling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

** End of SDS ***