

## **SN-504 SILICONE SEALANT - HIGH MODULUS**

### x'traseal®

### SAFETY **DATA SHEET**

**REV: 06** 

Date: 30 April 2024

### 1. Product & Company Identification

### **Product Details**

Product name: SN-504 Industrial Grade RTV Neutral Silicone Sealant - HM

Physical form:

**Low Oxime Odour** Odour:

CAS No.: **Mixture** 

### **Company Details**

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32, JalanTemenggong, Off JalanTampoi,

81100 Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545 / + 60-7-3337919

### 2. Hazards Identification

#### **Hazard Pictogram**



### Classification

| Skin corrosion or irritation         | Category 2 |
|--------------------------------------|------------|
| Serious eye damage or eye irritation | Category 2 |

#### **Hazard Statement**

H315 - Causes skin irritation.

H319 - Causes serious eye irritation

### <u>Precautionary Statement - Prevention</u>

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

<u>Precautionary Statement – Response</u> P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)

No. 32, Jalan Temenggong, Off Jalan Tampol, 81100 Johor Bahru, Johor, Malaysia. Tel: +607 333 1222 Fax: +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



# SN-504 INDUSTRIAL GRADE RTV NEUTRAL SILICONE SEALANT - HIGH MODULUS



### SAFETY DATA SHEET

**REV: 06** 

Date: 30 April 2024

Precautionary Statement - Storage

No precautionary statement

Precautionary Statement - Disposal

No precautionary statement

3. Composition / Hazardous Components

**Chemical Name** CAS No. WT% Methyl Tri (Methylethylketoxime) Silane 22984-54-9 1-8% Vinyl Tri (Methylethylketoxime) Silane 2224-33-1 1 - 5 % 68583-49-3 5 - 15 % **Treated Fume Silica** Linear Polydimethylsiloxanes 63148-62-9 10 - 45% Limestone 131765-3 20 - 45%

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap. In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media: Unknow

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide, nitrogen oxides and

formaldehyde.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during

processing. Wear safety shoes.

Protection against fire/ explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L drum.



## **SN-504 SILICONE SEALANT - HIGH MODULUS**

### x'traseal®

### SAFETY DATA SHEET

**REV: 06** 

Date: 30 April 2024

### 8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended General ventilation: Recommended

Hand protection: Suitable protective gloves. Eye protection: Safety/protective glasses.

Combustible Flammability:

Note: Until more data is known, exposure levels should be maintained as low as achievable.

#### 9. Physical and Chemical Properties

Paste Specific gravity:  $1.40 \pm 0.05$ Colour: **Matt Black** Not indicated. Viscosity: Odour: **Oxime Odour** 

Volatile, % volume (25°C): < 5%

Not Applicable. **Boiling point:** Flash point: Not Applicable. Ignition temperature: Not Applicable. Solubility in water: Insoluble Vapour pressure: Not Applicable. Solubility in organic solvent: Toluene.

Note: the above information is not intended for use in preparing specification.

### 10. Stability and Reactivity

Chemical stability: Stable Incompatibility (material to be avoid): None known. Conditions to be avoid: None known. **Dangerous reactions:** None known.

Dangerous products of decomposition: Ketoxime during curing.

### 11. Toxicological Information

Not determined Acute toxicity: Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization: Sensitization possible by inhalation.

**Additional Toxicological information:** Until more data is known, exposure levels should be maintained as low as

achievable.





# SN-504 INDUSTRIAL GRADE RTV NEUTRAL SILICONE SEALANT - HIGH MODULUS



### SAFETY DATA SHEET

**REV: 06** 

Date: 30 April 2024

### 12. Ecological Information

Complete information not yet available.

### 13. Disposal considerations

For cured sealant landfill may be suitable.

With respect to local regulation, dispose to suitable incineration plant.

### 14. Transport Information

Dangerous Goods by Road (ADR):
Proper Shipping Name:
Hazard class or division:
Identification number:
Packaging group:
Not regulated
Not regulated

International Air Transportation (ICAO/IATA):
Proper Shipping Name: Not regulated
Hazard class or division: Not regulated
Identification number: Not regulated
Packaging group: Not regulated

Water Transportation (IMO/IMDG):

Proper Shipping Name:
Hazard class or division:
Identification number:
Packaging group:

Not regulated
Not regulated

Not dangerous goods under the transport regulation.

### 15. Regulatory Information

Labeling (EC): This product is not subject to the labelling requirements.

### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\* End Of SDS \*\*\*