



SA-117

VERSATILE GRADE SILICONE SEALANT

x'traseal®

SAFETY DATA SHEET

REV: 02

Date: 30 April 2024

1. Product & Company Identification

Product Detail

Product name: SA-117 Versatile Grade RTV Acetic Silicone Sealant
Physical form: Paste
Odour: Vinegar Odour
CAS No.: Mixture

Company Details:

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.
H319 - Causes serious eye irritation

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



SA-117

VERSATILE GRADE SILICONE SEALANT

x'traseal®

SAFETY DATA SHEET

REV: 02

Date: 30 April 2024

P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Titanium dioxide	13463-67-7	< 5 %
Methyltriacetoxysilane	4253-34-3	< 5 %
Treated Fume Silica	68611-44-9	5 – 15 %
Petroleum Distillates	64742-48-9	5 – 30 %

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion:

Seek medical advice immediately.

In case of skin contact:

Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact:

Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media:

All standard fire-fighting media.

Unsuitable extinguishing media:

Unknown

Hazardous decomposition:

Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde

6. Accidental Release Measures

Methods for cleaning up:

Take up mechanically

7. Handling and Storage

Handling:

Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.

Protection against fire/ explosion:

General rules of fire prevention should be observed.

Storage:

Keep container tightly closed and dry.

Cautions:

Extreme heavy in drum form if product packed in 200L drum.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



SA-117

VERSATILE GRADE SILICONE SEALANT

x'traseal®

SAFETY DATA SHEET

REV: 02

Date: 30 April 2024

8. Exposure control / Personal protection

Ingredients with limited values to be controlled:	Not indicated
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves
Eye protection:	Safety/ protective glasses
Flammability:	Combustible

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	0.97 ± 0.05
Colour:	Clear and pigmented
Viscosity:	Not indicated
Odour:	Acetic vinegar
Volatile, % volume (25°C):	< 30%
Solubility in water:	Insoluble
Boiling point:	Non known
Flash point:	Non known
Ignition temperature:	Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	Water
Conditions to be avoid:	High temperature
Dangerous reactions:	None known
Dangerous products of decomposition:	Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes
On the eye:	Irritant effect
Sensitisation:	Sensitization possible by inhalation
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



SA-117

VERSATILE GRADE SILICONE SEALANT

x'traseal®

SAFETY DATA SHEET

REV: 02

Date: 30 April 2024

13. Disposal Considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations. Dispose to an authorised waste collection point. Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.

14. Transport Information

Dangerous Goods by Road (ADR):

Proper Shipping Name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packaging group:	Not regulated

International Air Transportation (ICAO/IATA):

Proper Shipping Name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packaging group:	Not regulated

Water Transportation (IMO/IMDG):

Proper Shipping Name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packaging group:	Not regulated

Not dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of SDS ***



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com