



x'traseal®

WP-715

XTRASLATE 208

TECHNICAL DATA SHEET

REV: 02

Date: 30 APRIL 2025

DESCRIPTION

WP-715 XTRASLATE 208 is a colorless acrylic clear coating with anti-staining properties. It provides protection and gives glossy finish to the coated substrates.

FEATURES

- Easy to use
- Fast drying
- Non-yellowing
- Dust-proof
- Good waterproof
- Indoor & outdoor use
- Excellent Weather Resistance

USES

WP-715 XTRASLATE 208 suitable for use on:

- Natural stones such as slates, sandstones
- Tiles & brickworks
- Paver tiles
- Terra cotta tiles

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

It cannot apply to non-porous substrate.

TECHNICAL & PHYSICAL DATA

Appearance	Liquid
Colour	Transparent
Odour	Solvent Odor
Application Temp.	5°C-45°C
Service Temp.	5°C-50°C
Drying time	2 hours
Bond Strength on concrete (7 days)	10kgf/cm ²
Consumption	0.15 kg/m ²
Shelf Life	12 Months

STORAGE

Material should be stored in a dry and cool place.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



WP-715

XTRASLATE 208

x'traseal®

TECHNICAL DATA SHEET

REV: 02

Date: 30 APRIL 2025

APPLICATION INFORMATION

SUBSTRATE PREPARATION

Prior to application, the substrate must be thoroughly clean and dry, free from algae, mildew, fungal, grease and oil. Do not apply **WP-715** on wet or damp materials.

APPLICATION

WP-715 can be applied on the substrate by brush roller and airless spray. The application work should be done at 5- 45°C. Extra **WP-715** layer needed when the substrate was not fully covered.

CLEANING OF TOOLS

Clean all tools and application equipment with thinner/ white spirit immediately after use.

TIPS

- Do not use at non porous material (eg: glass, plastic, metallic substrate)



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)

No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com