

SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

1. Product & Company Identification

Product Details

Product name: HEAVY DUTY GEAR OIL EP140 (API GL-5)
Physical form: Liquid
Odour: Light
CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

EYE IRRITATION - Category 2B
SKIN SENSITIZATION - Category 1
AQUATIC HAZARD (ACUTE) - Category 3
AQUATIC HAZARD (LONG-TERM) - Category 3

Hazard Statement

H315- Causes eye irritation.
H317- May cause an allergic skin reaction.
H412- Harmful to aquatic life with long lasting effects.

Precautionary Statement – Prevention

P280- Wear protective gloves.
P273- Avoid release to the environment.
P261- Avoid breathing vapor.
P264- Wash hands thoroughly after handling.
P272- Contaminated work clothing must not be allowed out of the workplace.

Precautionary Statement – Response

P302+P352- IF ON SKIN: Wash with plenty of soap and water.
P363- Wash contaminated clothing before reuse.



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

P333+P313- If skin irritation or rash occurs: Get medical attention.
P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313- If eye irritation persists: Get medical attention.

Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

P501- Dispose of contents and container in accordance with all local, regional, national and International regulations.

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
1-Propene, 2-methyl-, homopolymer	9003-27-4	25 - 50
Long-chain alkyl amine	68955-53-3	0.6 - 1
Long-chain alkenyl amine	112-90-3	0.3 - 0.7

4. First-aid Measures

Take off all contaminated clothing immediately.

Eye Contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Skin Contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

5. Fire Fighting Measures

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: None known.

Special firefighting procedure: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazardous decomposition: Decomposition products may include the following materials:
carbon dioxide
carbon monoxide



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

Specific hazards arising from the chemical:

This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

6. Accidental release measures

Methods for cleaning up:

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

7. Handling and Storage

Precautions for safe handling

Protective measures:

Put on appropriate personal protective equipment. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Avoid contact with used product. Do not reuse container.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure control / Personal protection

Control parameters

Occupational exposure limits:

Under conditions which may generate mists, the following exposure limits are recommended: ACGIH TLV TWA: 5 mg/m³ ; STEL: 10 mg/m³.

Appropriate engineering

Good general ventilation should be sufficient to control worker



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

controls:
Environmental exposure
controls:

exposure to airborne contaminants.
Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

9. Physical and Chemical Properties

Form:	Liquid
Colour:	clear
Odour:	Mild sulfur
Density, kg/litre @15°C	0.886
Flashpoint COC, °C:	230
Kinematic Viscosity ,mm ² /s @40°C	106.2
Kinematic Viscosity, mm ² /s @100°C	14.4
Pour Point, °C	-21

10. Stability and Reactivity

Reactivity:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability:	The product is stable.
Incompatibility (material to be avoid):	Oxidizing materials.
Conditions to be avoid:	Keep away from sources of ignition.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

Acute toxicity

There is no data available.

Carcinogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Name : Long-chain alkenyl amine
Category : Category 3
Route of exposure : Not applicable.
Target organs : Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name : Long-chain alkenyl amine
Category : Category 2
Route of exposure : Not determined
Target organs : Not determined

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Aspiration hazard

There is no data available.

Potential acute health effects

Eye contact : Causes eye irritation.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Skin contact : May cause an allergic skin reaction.

Delayed and immediate effects and also chronic effects from short and long term exposure

No known significant effects or critical hazards.

Potential chronic health effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

12. Ecological Information

Toxicity

Product/ingredient name : 1-Propene, 2-methyl-, homopolymer
Result : Acute LC50 >5600000 µg/l Fresh water



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

Species : Fish - Oncorhynchus mykiss
Exposure : 96 hours

Persistence and degradability
There is no data available.

Bioaccumulative potential
There is no data available.

Mobility in soil
Soil/water partition coefficient (K_{oc}) : There is no data available.
Other adverse effects : No known significant effects or critical hazards.

13. Disposal Considerations

Waste Disposal Method: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport Information

DOT shipping name : non-regulated
DOT label : not applicable
DOT identification No.: not applicable
Supplemental section 12 information:
IMDG, IATA/ICAO, TDG – non – regulated

15. Regulatory Information

U.S. Federal regulations :
United States inventory (TSCA 8b): All components are listed or exempted.
Clean Water Act (CWA) 311: Phenol; Naphthalene; Benzene; Ethylbenzene
Clean Water Act (CWA) 307: Propylene oxide; Phosphoric acid; Phenol; Naphthalene; Benzene; Ethylbenzene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed

16. Other Information



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

HEAVY DUTY GEAR OIL EP140(API GL-5)

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)

No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor Darul Takzim, Malaysia.

Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919

No.43, Jalan Tambur 33/19, Seksyen 33, Shah Alam Technology Park, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel : +603 5124 0876 / 5124 0878 Fax : +603 5124 0877

Mohm Chemical Sdn. Bhd. is an ISO 9001 certified company in Malaysia.

x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd.

©1993 Mohm Chemical Sdn. Bhd. All rights reserved.

Website: www.xtraseal.com Email : info@mochem.com