

## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

### 1. Product & Company Identification

#### Product Details

**Product name:** XM XTRA MILES SUPERIOR MINERAL ENGINE OIL  
SAE20W-50(API CF)  
**Physical form:** Liquid  
**Odour:** Mild hydrocarbon  
**CAS No.:** Mixture

#### Company Details

**Manufacturer:** Mohm Chemical Sdn Bhd  
**Address:** No. 32, Jalan Temenggong, Off Jalan Tampoi,  
81100 Johor Bahru, Johor, Malaysia.  
**Tel:** + 60-7-3331222  
**Fax:** + 60-7-3320545/ + 60-7-3337919

### 2. Hazards Identification

#### Hazard Pictogram

-  
**Signal Word:** -.

**Classification**  
Not classified.

**Hazard Statement**  
No precautionary statement

**Precautionary Statement – Prevention**  
No precautionary statement

**Precautionary Statement – Response**  
No precautionary statement

**Precautionary Statement – Storage**  
No precautionary statement

**Precautionary Statement – Disposal**  
No precautionary statement

### 3. Composition / Hazardous Components



## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

| <u>Chemical Name</u>        | <u>CAS No.</u> | <u>WT%</u> |
|-----------------------------|----------------|------------|
| Zinc Dialkyldithiophosphate | 84605-29-8     | 1- 2.5     |

### 4. First-aid Measures

Take off all contaminated clothing immediately.

|                |                                                                                                                                                                                                                                                        |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Contact :  | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.                                                                    |
| Skin Contact : | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.                                                                                                                         |
| Inhalation :   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.                                                                                                                          |
| Ingestion :    | Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. |

### 5. Fire Fighting Measures

|                                  |                                                                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media :   | Use an extinguishing agent suitable for the surrounding fire.                                                                                                       |
| Unsuitable extinguishing media : | None known.                                                                                                                                                         |
| Special firefighting procedure : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
| Hazardous decomposition :        | Carbon dioxide, carbon monoxide, smoke                                                                                                                              |

### 6. Accidental release measures

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods for cleaning up:   | Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor |
| Environmental precautions: | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).                                                                                                                                                                                                                                                   |

### 7. Handling and Storage

#### Precautions for safe handling

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| Protective measures: | Put on appropriate personal protective equipment. Avoid contact with |
|----------------------|----------------------------------------------------------------------|



## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

**Advice on general occupational hygiene:**

**Conditions for safe storage including any incompatibilities:**

used product. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure control / Personal protection

### Control parameters

**Occupational exposure limits:**

Under conditions which may generate mists, the following exposure limits are recommended: ACGIH TLV TWA: 5 mg/m<sup>3</sup> ; STEL: 10 mg/m<sup>3</sup>.

**Appropriate engineering controls:**

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure controls:**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### Individual protection measures

**Hygiene measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection:**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

**Hand protection:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection:**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection:**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:**

Not required under normal conditions of use.

## 9. Physical and Chemical Properties

|                                |                          |
|--------------------------------|--------------------------|
| <b>Form:</b>                   | <b>Liquid</b>            |
| <b>Colour:</b>                 | <b>Amber</b>             |
| <b>Odour:</b>                  | <b>Mild hydrocarbon.</b> |
| <b>Density, kg/litre @15°C</b> | <b>0.873</b>             |



## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

|                                   |       |
|-----------------------------------|-------|
| Flashpoint COC, °C:               | 220   |
| Kinematic Viscosity ,mm2/s @40°C  | 141.8 |
| Kinematic Viscosity, mm2/s @100°C | 17.7  |
| Pour Point, °C                    | -30   |

### 10. Stability and Reactivity

|                                         |                                                                                                      |
|-----------------------------------------|------------------------------------------------------------------------------------------------------|
| Reactivity:                             | No specific test data related to reactivity available for this product or its ingredients.           |
| Chemical stability:                     | The product is stable.                                                                               |
| Incompatibility (material to be avoid): | Oxidizing materials.                                                                                 |
| Conditions to be avoid:                 | Keep away from sources of ignition.                                                                  |
| Possibility of hazardous reactions:     | Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| Hazardous decomposition products:       | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

### 11. Toxicological Information

#### Acute toxicity

Product/ingredient name : Zinc Dialkyldithiophosphate

Result : LD50 Oral Rat

Species : Rat

Dose : 3.2 g/kg

Exposure : -

#### Carcinogenicity

There is no data available.

#### Irritation/Corrosion

There is no data available.

#### Sensitization

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### Aspiration hazard

There is no data available.

#### Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.



## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

Delayed and immediate effects and also chronic effects from short and long term exposure  
No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route : Oral  
ATE value : 189024.8 mg/kg

## 12. Ecological Information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name : Zinc Dialkyldithiophosphate  
LogP<sub>ow</sub> : 0.56  
BCF : -  
Potential : low

Mobility in soil

Soil/water partition coefficient (K<sub>OC</sub>) : There is no data available.  
Other adverse effects : No known significant effects or critical hazards.

## 13. Disposal Considerations

**Waste Disposal Method:** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport Information

DOT shipping name : non-regulated  
DOT label : not applicable  
DOT identification No.: not applicable  
Supplemental section 12 information:  
IMDG, IATA/ICAO, TDG – non – regulated



## SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

# XM XTRA MILES SUPERIOR MINERAL ENGINE OIL SAE20W-50(API CF)

### 15. Regulatory Information

#### U.S. Federal regulations :

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Zinc Dialkyldithiophosphate; Arsenic; Lead; Cadmium

(Non-pyrophoric); Benzene

Clean Water Act (CWA) 311: Benzene

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\*\* End Of SDS \*\*\*



**MOHM CHEMICAL SDN. BHD.** (REG NO 276851-U)

No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor Darul Takzim, Malaysia.

Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919

No.43, Jalan Tambur 33/19, Seksyen 33, Shah Alam Technology Park, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel : +603 5124 0876 / 5124 0878 Fax : +603 5124 0877

Mohm Chemical Sdn. Bhd. is an ISO 9001 certified company in Malaysia.  
x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd.

©1993 Mohm Chemical Sdn. Bhd. All rights reserved.  
Website: [www.xtraseal.com](http://www.xtraseal.com) Email : [info@mochem.com](mailto:info@mochem.com)