

TECHNICAL DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XP XTREME PERFORMANCE - FULLY SYNTHETIC

SAE5W-30 (API SN/ILSAC GF-4)

XP XTREME PERFORMANCE SAE 5W-30 premium quality fully synthetic motor oil that formulated using high performance additives for both diesel and gasoline engines. Provides significantly increased cleaning and protection properties, together with extra high thermal stability and also extends oil-drain intervals. Meets and exceeds API SN/ILSAC GF-4 standards. It features x'traseal exclusive "Low-SAPS" additive technology and a unique anti-wear system.

BENEFITS

- Ideal for high performance diesel and gasoline engines (both turbocharged and naturally aspirated).
- Maximized short and long term engine performance
- Reduces engines deposits to help maximize engine response
- Delivers complete across a variety of engines speed, conditions and temperatures
- Sustain maximum performance even during the most demanding driving condition

TYPICAL PROPERTIES FULLY SYNTHETIC MOTOR OIL

Characteristic	Unit	ASTM Method	RESULT
Colour			2.5
Specific Gravity @ 15°C			0.841
Kinematic Viscosity @ 100°C	cSt	D445	10.4
Kinematic Viscosity @ 40°C	cSt	D445	62.00
Viscosity Index			156
Flash Point COC, °C	°C		210
Pour Point	°C	D97	-33

Caution: Do not fill container with fuel /solvent- static could cause fire. Avoid prolong and repeat skin contact with the used oils. Protect the environment by disposing of used oil properly.

